



## Description

### 5 Megapixel GigE camera, ICX655 - PoE option

The Manta G-504B/C is a 5 Megapixel GigE Vision camera with the Sony ICX655 sensor. It runs at 9 fps (full resolution).



The camera incorporates three LUTs, sophisticated color correction algorithms, a robust metal housing, and many modular options like angled heads or board level versions. Manta cameras cover a wide range of imaging applications. The Manta is **now optionally available with PoE (Power over Ethernet)**.

- Sony ICX655 (type 2/3), 5 Megapixels
- Sync modes
  - Trigger ready, trigger input, exposing, readout, imaging, strobe, GPO
- Trigger
  - External trigger event: rising/falling/any edge, level high/low
  - External trigger delay: 0 to 60 seconds in 1  $\mu$ s increments
- Modular options
  - Various IR cut/pass filters
  - Board level version
  - Angled head
  - White medical design
  - **NEW: PoE (Power over Ethernet)**

## Specifications

Manta	G-504
<b>Interface</b>	IEEE 802.3 1000baseT
<b>Resolution</b>	2452 x 2056
<b>Sensor</b>	Sony ICX655
<b>Type</b>	CCD Progressive
<b>Sensor Size</b>	Type 2/3
<b>Cell size</b>	3.45 µm
<b>Lens mount</b>	C
<b>Max frame rate at full resolution</b>	9 fps
<b>A/D</b>	14 bit
<b>On-board FIFO</b>	32 MB
<b>Output</b>	
<b>Bit depth</b>	8-12 bit
<b>Mono modes</b>	Mono8, Mono16, Mono12 packed
<b>Color modes YUV</b>	YUV411, YUV422, YUV444
<b>Color modes RGB</b>	RGB24, BGR24
<b>Raw modes</b>	Bayer8, Bayer16, Bayer12 packed
<b>General purpose inputs/outputs (GPIOs)</b>	
<b>TTL I/Os</b>	0
<b>Opto-coupled I/Os</b>	2 inputs, 2 outputs
<b>RS-232</b>	1
<b>Power/Mass/Dimensions/Regulations</b>	
<b>Power requirements (DC)</b>	8 V - 30 V
<b>Power consumption (12 V)</b>	<3.6 W
<b>Mass</b>	<200 g
<b>Body Dimensions (L x W x H in mm)</b>	86.4 x 44 x 29 mm incl. connectors
<b>Regulations</b>	CE, FCC Class B, RoHS

[Download Manta technical drawing \(click here\)](#)



## Smart features

- ROI (Region of Interest Readout)
- Exposure
  - Auto/one push/programmable
  - Exposure time 38  $\mu$ s to 60 s
- White balance
  - Auto/one push/programmable
- On-board debayering
- Hue, saturation, sharpness (color versions)
- Gain
  - Auto/one push/programmable
  - Manual gain control: 0 to 32 dB (1 dB/step)
- Three look-up tables (LUTs), gamma correction
- DSP subregion (selectable ROI for auto features)
- Binning (up to 8 x 14, independent x and y binning)
- Sub-sampling (decimation)
- Stream hold
- StreamBytesPerSecond (easy bandwidth control)
- Event channel
- Chunk data
- 5 storable user sets

## Applications

The Manta G-504B/C is a 5 Megapixel GigE Vision camera with an outstanding price/performance ratio. On request, board level versions with separate sensor head (up to 200 mm distance to camera mainboard) are available. Thanks to the three LUTs (separate R, G, and B control), color correction features and the PoE option, this Manta camera suits a large variety of imaging applications.

Applications:

- Industrial inspection with high resolution
- Automation
- Logistics
- Science and research
- Healthcare and medical
- ITS (Intelligent traffic solutions)
- ... and many more